






POP DOWN® BATH OVERFLOW KIT

(For the 21831)

CODE	OUTLET SIZE	FINISH	CTN QTY
21832.01	40mm	Chrome	20

Flow Rate of 12 Litres per minute when a sustained water head of 150mm is applied. The stated flow rate is dependent on the shape of the material vessel it is used with, along with the drainage configuration downstream of the waste. Other installation factors may impact the stated flow rate.



21832

(TO BE USED WITH 21831 ONLY)

Available Finishes



Note: .04 Polished Brass (Raw/Living Finish)



ART INTERNATIONAL
PLUMBING & BATHROOMWARE

134 Gilba Road Girraween, NSW 2145
P: 02 9896 7760 | F: 02 9636 2498 | sales@artinternational.com.au
www.artaust.com.au | www.artnz.co.nz



ART PLUMBING PRODUCTS
Innovative Plumbing Fittings



BOUNTY BATHROOMWARE
Designer Bathroom Fittings

1. Introduction

Art Plumbing Products and Bounty Bathroomware products are manufactured using carefully chosen materials to provide good looks and durability, whilst also complying with the appropriate Australian Standards. Treated with care, our products will offer many years of trouble free service. In order to preserve appearance with minimum effort, we offer the following advice. These recommendations are intended to assist you and are based on our experience and judgment but must not be regarded as amounting to a legal warranty or liability on our part.

2. Environmental Attack

This is caused by chemicals and particles that are present naturally in the air or are caused by activities that release these into the air. The chemicals and particles settle on surfaces and can cause irreversible damage. Areas of high exposure and thus high risk would include those near to the sea, mining activities, high traffic-flow, etc. Particular activities such as fumigation, building activities, chemical leaks, etc. can also cause high exposure. If you live in an area of high exposure or have an incident that causes high exposure you may need to clean more regularly.

3. Cleaning

- Electroplated brass finishes should only be cleaned using a soft cloth and a warm soapy water solution. Surfaces should then be rinsed with clean water and finally dried with a clean soft cloth.
- Avoid using strong chemicals (containing Chlorides, Citric Acid, Acetic Acid or other corrosive substances), abrasives cleaners and scourers.
- Where any chemicals are used in the bath (including bath salts, bubble bath, or cleaning agents), the waste should be thoroughly rinsed with fresh water after the bath is emptied.
- Polishing of Stainless Steel products is recommended utilising any of the commonly available Stainless Steel polishes.
- Chemicals used in the construction process such as Hydrochloric or Muriatic Acid (used to clean tile grout or masonry) that come in contact with Stainless Steel or Electroplated Brass will cause damage and void the product's warranty.